

# SURVEY RECOVERY FORM

City of Everett  
Department of Public Works

State of Washington  
County: Snohomish

Station Name: 729 03 01

Horizontal Datum: NAD 83/91

Vertical Datum: NAVD 88

Control Point ID: 729 Book:

Page: 03

Pt#: 01

Established By: Perteet Eng.

Date: 2/28/02

Edited by Geodetic Consultants 06/03/2002

Section: 29

Township: 29 N

Range: 05 E

LATTITUDE: (5 decimal places) 47 58 31.38753  
LONGITUDE: (5 decimal places) 122 11 57.36735

ORTHOMETRIC HEIGHT: \_\_\_\_\_ Feet  
\_\_\_\_\_ Meters

## Washington State Plane Coordinates – North Zone

	Northing (4 decimal places)	Easting (4 decimal places)	Point Scale Factor (to 9 decimal places)	Convergence Deg Min Sec
Feet	358759.839	1305866.941	0.999945335	-01 01 01.1
Meters	109350.2175	398029.3096		

### HORIZONTAL DATA:

Horizontal position established by:

\_\_\_\_\_ resection survey, comments \_\_\_\_\_

☒ GPS survey, GPS adjustment software used: Leica SKI-Pro V2.1

\_\_\_\_\_ other, explain: \_\_\_\_\_

surveyor's estimated relative positional accuracy: .1 ft. @ \_\_\_\_\_ 95% confidence

surveyor's estimated absolute positional accuracy: \_\_\_\_\_ ft. @ \_\_\_\_\_ % confidence

### VERTICAL DATA:

Vertical position established by:

\_\_\_\_\_ differential leveling to: \_\_\_\_\_ order accuracy

\_\_\_\_\_ GPS survey, accuracy within \_\_\_\_\_ ft \_\_\_\_\_ meters

surveyor's estimated relative positional accuracy: \_\_\_\_\_ ft @ \_\_\_\_\_ 95% confidence

surveyor's estimated absolute positional accuracy: \_\_\_\_\_ ft @ \_\_\_\_\_ % confidence

## MONUMENT DESCRIPTION

A concrete monument with a 2 inch brass disk with a punch set under an iron monument case and cover

### TO REACH

Located on the centerline of the intersection of Smith Avenue and 32<sup>nd</sup> street.

### REFERENCES

Az from North	Distance	Reference Description
N	12.5 feet	Sanitary Sewer Manhole Cover

Month & Year Recovered:

Condition of Mark:

Recovered By: